

FLUID APPLICATIONS TEST DATA SHEET

PRODUCT	% DILUTION	EQUIPMENT MODEL	GUN MODEL	PRESSURE	NOZZLE SIZE
BASE COAT - ESTERNI <i>F.12 QUARZO PRIMER</i>	1%	MINIPEGASO Pneumatic texture sprayer	TURBO GUN	Air pump 2 bar Air gun atomization 6,5 bar (Partially open recirculation valve)	Ø 4 mm
BASE COAT - ESTERNI <i>F.12 SILCOLOR PRIMER</i>	1%	MINIPEGASO Pneumatic texture sprayer	TURBO GUN	Air pump 2 bar Air gun atomization 6,5 bar (Partially open recirculation valve)	Ø 4 mm
BASE COAT - ESTERNI <i>F.12 SILCOLOR PRIMER PLUS</i>	1%	MINIPEGASO Pneumatic texture sprayer	TURBO GUN	Air pump 2 bar Air gun atomization 6,5 bar (Partially open recirculation valve)	Ø 4 mm
PITTURE - ESTERNI <i>F.12 QUARZO PITTURA</i>	10%	GIOTTO Airless electric diaphragm pump	AT250	200 bar	LASFC 19-40
PITTURE - ESTERNI <i>F.12 SILCOLOR PITTURA PLUS</i>	10%	GIOTTO Airless electric diaphragm pump	AT250	200 bar	LASFC 19-40
PITTURE - ESTERNI <i>F.12 SILCOLOR EXTRA PITTURA PLUS</i>	10%	GIOTTO Airless electric diaphragm pump	AT250	200 bar	LASFC 19-40
PITTURE - ESTERNI <i>F.12 ELASTOFLEX PITTURA PLUS</i>	▪	GIOTTO Airless electric diaphragm pump	AT250	220 bar	LASFC 19-40

FLUID APPLICATIONS TEST DATA SHEET

PRODUCT	% DILUTION	EQUIPMENT MODEL	GUN MODEL	PRESSURE	NOZZLE SIZE
RIVESTIMENTI A SPESSORE <i>F.12 QUARZO TONACHINO 1.2 mm</i>	2%	MINIPEGASO Pneumatic texture sprayer	TURBO GUN	Air pump 4 bar <i>Air gun atomization 6 bar</i> (Partially open recirculation valve)	Ø 8 mm
RIVESTIMENTI A SPESSORE <i>F.12 QUARZO TONACHINO 1.5 mm</i>	2%	MINIPEGASO Pneumatic texture sprayer	TURBO GUN	Air pump 5 bar <i>Air gun atomization 7 bar</i> (Partially open recirculation valve)	Ø 8 mm
RIVESTIMENTI A SPESSORE <i>F.12 QUARZO TONACHINO S 1.2 mm</i>	2%	MINIPEGASO Pneumatic texture sprayer	TURBO GUN	Air pump 4 bar <i>Air gun atomization 6 bar</i> (Partially open recirculation valve)	Ø 8 mm
RIVESTIMENTI A SPESSORE <i>F.12 QUARZO TONACHINO S 1.5 mm</i>	2%	MINIPEGASO Pneumatic texture sprayer	TURBO GUN	Air pump 5 bar <i>Air gun atomization 7 bar</i> (Partially open recirculation valve)	Ø 8 mm
RIVESTIMENTI A SPESSORE <i>F.12 SILCOLOR TONACHINO PLUS 1.2 mm</i>	2%	MINIPEGASO Pneumatic texture sprayer	TURBO GUN	Air pump 4 bar <i>Air gun atomization 6 bar</i> (Partially open recirculation valve)	Ø 8 mm
RIVESTIMENTI A SPESSORE <i>F.12 SILCOLOR TONACHINO PLUS 1.5 mm</i>	2%	MINIPEGASO Pneumatic texture sprayer	TURBO GUN	Air pump 5 bar <i>Air gun atomization 7 bar</i> (Partially open recirculation valve)	Ø 8 mm
RIVESTIMENTI A SPESSORE <i>F.12 SILCOLOR TONACHINO 1.2 mm</i>	2%	MINIPEGASO Pneumatic texture sprayer	TURBO GUN	Air pump 4 bar <i>Air gun atomization 6 bar</i> (Partially open recirculation valve)	Ø 8 mm

FLUID APPLICATIONS TEST DATA SHEET

PRODUCT	% DILUTION	EQUIPMENT MODEL	GUN MODEL	PRESSURE	NOZZLE SIZE
RIVESTIMENTI A SPESSORE F.12 QUARZO TONACHINO 1.2 mm	2%	MINIPEGASO Pneumatic texture sprayer	TURBO GUN	Air pump 4 bar Air gun atomization 6 bar (Partially open recirculation valve)	Ø 8 mm
RIVESTIMENTI A SPESSORE F.12 SILCOLOR TONACHINO PLUS 1.5 mm	2%	MINIPEGASO Pneumatic texture sprayer	TURBO GUN	Air pump 5 bar Air gun atomization 7 bar (Partially open recirculation valve)	Ø 8 mm
RIVESTIMENTI A SPESSORE F.12 SILCOLOR TONACHINO 1.2 mm	2%	MINIPEGASO Pneumatic texture sprayer	TURBO GUN	Air pump 4 bar Air gun atomization 6 bar (Partially open recirculation valve)	Ø 8 mm
RIVESTIMENTI A SPESSORE F.12 ELASTOFLEX TONACHINO PLUS 1.2 mm	2%	MINIPEGASO Pneumatic texture sprayer	TURBO GUN	Air pump 5 bar Air gun atomization 7 bar (Partially open recirculation valve)	Ø 8 mm
BASE COAT-INTERNI F.14 AQUACOLOR PRIMER	5 ÷ 10 %	GIOTTO Airless electric diaphragm pump	AT250	220 bar	LASFC dal 17-40 al 21-40
PITTURE - INTERNI F.14 AQUACOLOR PITTURA	5 ÷ 10 %	GIOTTO Airless electric diaphragm pump	AT250	220 bar	LASFC dal 17-40 al 21-40
PITTURE - INTERNI F.14 CERCOLOR PITTURA PLUS	5 ÷ 10 %	GIOTTO Airless electric diaphragm pump	AT250	220 bar	LASFC dal 17-40 al 21-40
PITTURE - INTERNI F.14 CERCOLOR PITTURA	5 ÷ 10 %	GIOTTO Airless electric diaphragm pump	AT250	220 bar	LASFC dal 17-40 al 21-40